


## SL181876-E

### Cylindrical roller bearing

Schaeffler Kimliği:  
0153798840000

Cylindrical roller bearing SL1818..-E, full complement roller set, single row, semi-locating bearing, 1 rib on outer ring, 2 ribs on inner ring, type SL18

### Teknik bilgiler



### Dimensions

$r_{\min}$	2,1 mm	Minimum chamfer dimension
s	4 mm	Axial displacement
$d_1$	415,5 mm	Maximum rib diameter inner ring
$D_{1\min}$	448 mm	Minimum rib diameter outer ring
E	459 mm	Raceway diameter outer ring
	18,5 kg	Ağırlık

### Main Dimensions & Performance Data

d	380 mm	Bore diameter
D	480 mm	Outside diameter
B	46 mm	Width
$C_r$	650.000 N	Basic dynamic load rating, radial
$C_{0r}$	1.290.000 N	Basic static load rating, radial
$C_{ur}$	133.000 N	Fatigue load limit, radial
$n_G$	710 1/min	Limiting speed
$n_{gr}$	490 1/min	Reference speed

### Mounting dimensions

$d_{a\min}$	415,5 mm	Minimum diameter shaft shoulder
$d_{c\min}$	415,5 mm	Minimum shaft shoulder
$D_{a\max}$	448 mm	Maximum diameter of housing shoulder
$D_{e\min}$	459 mm	Minimum diameter of housing shoulder
$r_{a\max}$	2,1 mm	Maximum recess radius

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

